

In The Claims

Prior to examination and calculation of fees, please cancel claims 1 through 14;
claims 15-31 remain.

1-14. Cancelled.


15. A method of hydraulically fracturing a subterranean coal bed, comprising the step of injecting a well treatment fluid composition via a wellbore into a subterranean coal bed at a flow rate and pressure sufficient to hydraulically fracture the formation, wherein the well treatment fluid composition comprises a carrier fluid and an amphoteric surfactant.
16. The method of claim 15, wherein the well treatment fluid further comprises proppant.
17. The method of claim 15, wherein the well treatment fluid further comprises a viscosifying agent.
18. The method of claim 15, wherein the composition is a foam that comprises a gas selected from the group consisting of nitrogen, air, and carbon dioxide.
19. The method of claim 15, further comprising injecting carbon dioxide via the wellbore into the subterranean bed prior to injecting the well treatment fluid composition.
20. The method of claim 15, wherein the surfactant comprises an alkyl-aminocarboxylic acid or carboxylate.
21. The method of claim 15, wherein the surfactant has the formula $RNH_2(CH_2)_nC(O)OX$ wherein R is a saturated or unsaturated alkyl group having

from 6-20 carbon atoms, n is from 2-6, and X is hydrogen or a salt forming cation.

22. The method of claim 21, wherein n is from 2-4.
23. The method of claim 21, wherein R is a saturated or unsaturated alkyl group having from 10-14 carbon atoms.
24. The method of claim 15, wherein the surfactant comprises an alkyl-aminopropionic acid or propionate.
25. The method of claim 15, wherein the surfactant is a coco-aminopropionate.
26. The method of claim 17, wherein the viscosifying agent is a solvatable, crosslinkable polymer selected from the group consisting of guar, hydroxypropyl guar, carboxymethyl guar, carboxymethylhydroxypropyl guar, hydroxyethyl cellulose, carboxymethylhydroxyethyl cellulose, hydroxypropyl cellulose, xanthan, and mixtures thereof.
27. The method of claim 26, further comprising a crosslinking agent.
28. The method of claim 27, further comprising a gel breaker for the viscosifying agent.
29. The method of claim 28, further comprising a breaker aid.
30. The method of claim 15, further comprising an additive that decreases the frictional pressure involved in pumping the fluid composition through well tubing.
31. The method of claim 30, wherein the additive comprises at least one polyacrylamide.

PATENT
Attorney Docket No. 56.0553DIV of CIP
Inventors: England, et al.
Express Mail No.: ER442604184US

Respectfully submitted,



Thomas O. Mitchell
Reg. No.: 47,800
Agent for Applicant(s)

Date: Feb. 10, 2004

Schlumberger Technology Corporation
IP Dept., Well Stimulation
110 Schlumberger Drive, MD1
Sugar Land, Texas 77478
Ph: (281) 285-4490
Fax: (281) 285-8569